

Built to LAST!
Industrial Equipment
 WATER CLEANING SYSTEMS
Since 1987

Environmental Cleaning Systems
Only Sales, Parts & Service Center from Sac. CA to Oregon!

 **Parts Washers** 830 Cherry Street
 Chico. CA 95928
 PH: (800)287-8306
 (530)893-2125
 Fax: (530)893-1035
 www.industrial-equipment.biz
 **Pressure Washers**
 **Water Treatment** Lic# 795757

TOP LOAD AQUEOUS PARTS WASHERS

**TL Series Parts Washers are Heavy Duty Machines
 Built with Industrial Customers Use in Mind**

Clean greasy grimy mechanical parts in minutes with hot water and biodegradable detergents instead of using solvents.

Simply place your parts in the washer, close the door, set the timer, and in minutes your parts are clean.

Save Money!
 Save Labor!
 It's automatic.

Load it!
 Set and Forget it!



TL-72 shown

TL Series comes standard with:

- ◆ Mechanical Door Seal - No rubber seals to replace or leak!
- ◆ Swing Away Top Manifold - Top manifold swivels for easy loading/unloading clearance
- ◆ Low Water Shut-Off - Protect your heat elements from low water conditions
- ◆ Bushed Stainless Steel V-Jet Nozzles - Durability and precise 360 degree cleaning coverage.
- ◆ Gear Drive Turntable - Overcurrent protection, eliminates slippage associated with friction drive systems.
- ◆ Strut or Hydraulic Actuated Lid - TL-42 and larger have hydraulic actuated lids as standard
- ◆ Vertical Sealless Pump - No seals to leak or replace.
- ◆ Debris Screen - Keeps tanks free of larger debris.
- ◆ Simple Plug-N-Play makes options easy to install in-field.

Optional Equipment:

- ◆ Stainless Steel Construction
- ◆ Disc Style Stainless Oil Skimmer
- ◆ Custom Part Fixturing & Spray Manifolds
- ◆ Fresh Water or Re-circulating Rinse Options
- ◆ Compressed Air or Regenerative Blow-Off Systems
- ◆ High Pressure/Flow Pumps
- ◆ Auto Water Fill
- ◆ Low Water Fill
- ◆ Particulate Bag Filtration
- ◆ 1 or 2 Function Timers
- ◆ Insulation Packages
- ◆ Power Disconnect

TL-36 shown



TL-Series Model No.	Turntable Dia in	Working Height in	Load Capacity lbs	Vert Pump Motor Size hp	Pump Output psi / gpm	Solution Capacity gal	Heat Source kW	Lid Operation Type
TL-21	21	31	500	1.5	42 / 24	32	6	Strut Assist
TL-25	25	32	1,000	3	42 / 35	85	9	Strut Assist
TL-31	31	32	1,000	3	52 / 35	125	12	Strut Assist
TL-36	36	32	1,500	5	80 / 85	170	18	Strut Assist
TL-42	42	36	1,500	7.5	75 / 120	220	18	Hydraulic
TL-50	50	36	1,500	10	75 / 150	290	36	Hydraulic
TL-60	60	36	1,500	15	75 / 200	390	36	Hydraulic
TL-72	72	36	2,000	15	75 / 200	530	36	Hydraulic