

Built to LAST!
Industrial Equipment
WATER CLEANING SYSTEMS
Since 1987

Environmental Cleaning Systems
Only Sales, Parts & Service Center from Sac. CA to Oregon!

 **Parts Washers** 830 Cherry Street
 **Pressure Washers** Chico, CA 95928
 **Water Treatment** Lic# 795757 www.industrial-equipment.biz

PH: (800)287-8306
 (530)893-2125
 Fax: (530)893-1035

CONE BOTTOM STORAGE TANKS



Cone bottom tanks are an effective means for separating solids from water. The steep slope of the cone tank bottoms enhances separation and allows solids to be decanted through a valve in the bottom. This can be automated upon request.

notes	Nominal Capacity (gal)	Slope Degrees	Approx O.D.	Overall Height w/ Stand	Lid Size
M	6,850	60	10'-1"	20'-3"	24"
M	5,550	30	10'-0"	15'-4"	24"
m	3,000	50	7'-6"	13'-6"	16"
m	2,300	50	7'-6"	11'-4"	16"
m	1,600	50	7'-6"	9'-1"	16"
m	1,100	50	7'-6"	7'-6"	16"
	1,070	45	5'-1"	12'-2"	17"
	735	45	5'-1"	9'-11"	17"
	700	60	4'-4"	10'-10"	24"
P	615	44	4'-0"	10'-9"	17"
	500	60	4'-4"	8'-7"	24"
P	335	44	4'-0"	7'-9"	17"
	230	60	2'-8"	8'-10"	** 8"/16"

M = Molded-In Lifting Lugs Standard **m = Molded-In Lifting Lugs Available**
P = Optional Plastic Stand Available **** Larger Diameter Lid Optional**

The tanks shown in above chart are all closed-top tanks.

Cone bottom tanks range in size from 55 gallon to 6,850 gallons. Stands are required for proper support. Seismic stands are also available. Tanks are available in either linear or cross-linked polyethylene.