

# 8000

SERIES

**AALADIN ALL ELECTRIC PRESSURE WASHERS**

# Aaladin<sup>®</sup>

**CLEANING SYSTEMS**



- Instant Heat
- No Hot Exhaust
- No Smoke
- No Odor
- No Fumes
- Quiet
- Easy To Operate
- Removable Heating Elements
- Easy Maintenance
- Compact Cabinet Design
- Reliable
- Efficient
- System Protection Devices

YOU CAN DO MAGIC

# It's Electric

Our 8000 Series hot water washers are electrically heated and monitored for the ultimate in high pressure cleaning equipment.

The 8000 Series pressure washers are revolutionary hot water washers equipped with heavy-duty, removable high pressure heating elements which heat water instantly. Plus, our exclusive system protection devices monitor water flow, water pressure and water temperature to keep your washer running strong.

A powerful washer, the 8000 Series washer is capable of producing pressure from 1200 to 3000 PSI and water flow from 2.0 to 4.0 gpm. It is ideal for those situations when open flames or exhaust cannot infiltrate the cleaning area. This unit's innovative design includes state-of-the-art controls and safety features as well as a heating chamber constructed with removable elements for easy access.

All machine controls are 24 volt and optional remote controls are available.

When the cleaning job calls for an ultra-reliable, electrically-heated hot water washer, make sure it's an Aaladin 8000.

## Standard Features:

- Enclosed Heating Chamber
- Zero Pressure Unloader
- Triplex Ceramic Plunger Belt Driven Pump
- Low Water Shut Off Protection
- Quick Coupled Stainless Steel Nozzles
- Washer Fail-Safe Monitoring System
- Calibrated Detergent Mixing Valve
- Heavy Duty Legs
- Unitized High Pressure Heating Manifold
- Dual Temperature Hi-Limit Control
- Trigger Gun Control
- Reduced Flow Protection
- Automatic Shut Down Timer
- 24 Volt Controls
- Lighted Solenoid-Controlled Detergent System
- Stainless Steel Panels and Hood
- Incoloy Encased Elements
- Pressure Relief Valve
- Stainless Steel Float Tank
- Wire Braid Discharge Hose
- Watertight Electrical Panel
- Diagnostic Control Monitoring Lights
- Heavy Duty Tubular Steel Frame
- Powder Coat Paint

## Optional Features:

- Hour Meter
- 230 Volt 3 Phase
- Remote 2-Way
- Soap Solenoid

## Specifications:

MODEL	8212	8320	8430
KW	30 kw	60 kw	60 kw
FLOW OUTPUT (GPM)	2	3	4
PRESSURE RATINGS (PSI)	1200	2000	3000
PUMP TYPE	Ceramic Plunger	Ceramic Plunger	Ceramic Plunger
MOTOR HORSEPOWER	4	4	7.5
VOLT	240/480	240/480	240/480
AMP DRAW	80/40	170/85	180/90
PHASE	3	3	3
HEAT RISE*	110°	140°	110°
DISCHARGE HOSE	3/8" x 50'	3/8" x 50'	3/8" x 50'
APPROXIMATE WEIGHT (LBS)	330	370	470
<b><i>DIMENSIONS</i></b>			
LENGTH	32"	32"	32"
WIDTH	24"	24"	24"
HEIGHT	48"	48"	48"

\*Heat Rise plus incoming water temperature will equal the outgoing hot water temperature. Maximum 210°.

Distributed by: **Industrial Equipment**  
830 Cherry Street  
Chico, CA 95928  
(800) 287-8306



SOUTHEAST INTERSECTION, I-29 EXIT 15  
32584 477TH AVE., ELK POINT, SD 57025

PHONE 605.356.3325 FAX 605.356.2330  
1.800.356.3325

[www.aaladin.com](http://www.aaladin.com)