

# Natural Gas- or Propane-Heated Hot Water Pressure Washer Ideal for Indoor Cleaning



## Stationary Natural Gas-Heated Hot Water Pressure Washer with an Option to Add Multiple Remote Washing Stations

Our natural gas- or propane-heated models are ideal for indoor cleaning with hot water. They pack cleaning power of up to 3000 PSI yet fit within a small footprint. Powered

- 230V, 460V and 575V
- Belt-Drive Kärcher Pump with 7-Year Warranty
- Heated with Natural Gas or LP Gas
- High-Efficiency Burner with Standing Pilot
- Remote Wash Station Option

by electricity in a variety of configurations, all models feature an industrial belt-drive Kärcher high-pressure pump, a Schedule 80 steel heating coil and a high-efficiency burner with standing pilot. All are ETL certified to UL and CSA safety standards and can be fitted with up to four remote cleaning stations. Other options include stainless steel cabinet and coil wrap, hot water steam, time-delay shutdown, and even a wheel kit.

### TYPICAL APPLICATIONS

- Food Processing
- Agriculture
- Pens and Corrals
- Nurseries, Turf
- Manufacturing
- Marinas
- Golf Courses
- Meat Plants

### WHY KÄRCHER



Kärcher is the most trusted name in pressure washers—a fact confirmed when Kärcher was the only brand

selected to clean the famous Mount Rushmore National Monument in 2005.

Founder Alfred Kärcher invented hot water pressure washing in 1950. Today, as the world's largest manufacturer of pressure washers, Kärcher is the recognized innovative leader in the industry with over 300 patents.



**Dimensions:**  
44"L x 28"W x 49"H

- Industrial electric **motor** with multiple voltage options and thermal overload protection
- High-efficiency **burner** with standing pilot for reliable and affordable operation
- Industrial-grade, tri-plunger, oil-bath, belt-drive, **Kärcher pump** with 7-year warranty and cast iron **pulley system** that features cool-operating V-belts and an easy-to-adjust TrueTrak belt tension device

- Durable and ventilated **steel cabinet** with epoxy, powder coat finish; side panel is easy to remove for servicing
- Insulated Schedule 80 **heating coil** is made of 1/2-inch steel pipe and cold rolled; comes standard with stainless steel coil wrap and 5-year warranty
- Water resistant **control panel** with adjustable thermostat, hour meter and on/off switches for the burner and pump
- Thermal **pump saver valve** protects against hot-water damage by venting recirculated water
- High pressure **rupture disc** rated to 7000 lbs. for operator protection
- 50 ft. of extra-durable, wire-braid **hose** rated for 3000 PSI and with hose guard for burst protection
- Brass, anti-syphon **detergent metering valve** locks out air and dispenses precise amount of cleaning agent
- Insulated stainless steel **wand**

Model	Order No.	GPM	PSI	HP	Electrical	Amps	Pump	BTU	Ship Wt
HDS NG 3.5/20 Ea ST	1.575-701.0	3.5	2000	5	230V / 1 ph	22	Kärcher KD	353,125	741 lbs
HDS NG 3.9/20 Ea ST	1.575-702.0	3.9	2000	6.2	230V / 1 ph	29	Kärcher KM	407,754	801 lbs
HDS NG 5.0/20 Ea ST	1.575-705.0	5.0	2000	8.2	230V / 1 ph	36	Kärcher KM	478,134	844 lbs
HDS NG 5.0/20 Eb ST	1.575-706.0	5.0	2000	7.5	230V / 3 ph	25	Kärcher KM	478,134	814 lbs
HDS NG 5.0/20 Ec ST	1.575-707.0	5.0	2000	7.5	460V / 3 ph	13	Kärcher KM	478,134	795 lbs
HDS NG 3.5/30 Ea ST	1.575-708.0	3.5	3000	8.2	230V / 1 ph	36	Kärcher KM	353,125	835 lbs
HDS NG 3.5/30 Eb ST	1.575-709.0	3.5	3000	7.5	230V / 3 ph	25	Kärcher KM	353,125	810 lbs
HDS NG 4.8/30 Eb ST	1.575-711.0	4.8	3000	10	230V / 3 ph	28	Kärcher KM	455,883	810 lbs
HDS NG 4.8/30 Ec ST	1.575-712.0	4.8	3000	10	460V / 3 ph	15	Kärcher KM	455,883	823 lbs
HDS NG 4.8/30 Ef ST	1.575-713.0	4.8	3000	10	575V / 3 ph	13	Kärcher KM	455,883	817 lbs

YOUR AUTHORIZED KÄRCHER DEALER:



Kärcher Commercial Pressure Washers  
www.karchercommercial.com  
info@karchercommercial.com  
888-805-9852 • Fax 800-248-8409