

LANDA®

Industrial Pressure Washers
...Built Right to Do the Job Right

Since 1969

Distributed by
Industrial Equipment 800-287-8306
830 Cherry St, Chico, CA 95928
www.industrial-equipment.biz

HS

Oil-Heated, Hot Water Generator That Attaches to a Cold Water Pressure Washer

- Up to 3,000 PSI
- Increases incoming water temperature by up to 150°F
- Sch. 80 Heating Coil
- Tubed Pneumatic Tires

HOW IT IS USED

The HS-3000 is an electric-powered, diesel/oil-heated hot water generator that attaches to a cold-water pressure washer essentially turning it into a hot water pressure washer.

The HS-3000 does not have a pump but simply heats the pressurized water—as much as 150°F above the water's ambient temperature, depending on the flow rate—so it can be used for cleaning the toughest of cleaning challenges.

Even though it is more like an accessory, the HS-3000 is packed with all of the quality components that have established the built-to-last reputation for LANDA equipment, including Schedule 80 heating coil, tubed pneumatic tires, and high-efficiency burner.



■ Extra-durable **Heating Coil** made of leak-free, cold-rolled, Schedule 80 steel pipe with five-year warranty.

■ Rust-free, 11-gallon **Fuel Tank** with elevated fuel line to prevent dirt and debris from reaching burner.

■ Helpful **Tri-Lingual Labels** with operating instructions in English, Spanish and French for owner and operator protection.

■ 9 feet of wire-braid, **Hose** with coupler for connecting to cold water pressure washer.

■ **Triple Safety Protection**, including a rupture disk, high-limit thermostat and flow switch to prevent the build up of excessive pressures or heat.

■ 36 feet of high-grade Electrical Cord with **Ground Fault Circuit Interrupter** for operator safety.

■ High-efficiency **Burner** is easy to access and is protected by coil wrap hood.

■ Two-ply, tubed **Pneumatic Tires** make for easy maneuvering in any terrain.

■ Rugged 12-gauge steel **Chassis** protected by weather-resistant epoxy powder coat paint.



HS-3000 Specifications

Feature	HS-3000
Part Number	1.103-900.0
GPM	Up to 6
PSI	Up to 3,000
Temperature Rise*	Up to 150° F
Fuel Tank Capacity	11 Gallons
Electrical	120V, 1 ph, 5 amps
BTU Per Hour	420,000
Dimensions LxWxH	48" x 30" x 35"
Ship Weight	390 lbs.

* Variable depending on flow rate (3-6 GPM)

OPTIONS: (SEE YOUR LANDA DEALER FOR A COMPLETE LIST OF OPTIONS)

Part No.	Description
8.903-530.0	Stainless steel outer coil wrap
8.931-276.0	Stainless steel top wrap with black bottom wrap
8.711-858.0	175 ft Cox hose reel

Note: LANDA is constantly improving and updating its products. Consequently, pictures, features, and specifications in this brochure may differ slightly from current models. Flow rates and pressure ratings may vary due to variances allowed by manufacturers of our machine components. LANDA product performance is certified by the Cleaning Equipment Trade Association (CETA) to be within 5% of listed specifications.

www.landa.com