

# Wall-Mount Corona Discharge



The Wall-Mount ozone generators from ClearWater Tech offer corona discharge technology. This series has seven models to choose from. With an output range of 2.8 to 27 grams per hour, these units are equipped with universal input power supply or solid state current limit circuitry. Options include a built-in air preparation system, fully-adjustable 0-100% ozone output and 4-20 mA control.

*"I'd tried several ozone manufacturers before I found ClearWater Tech. ClearWater's ozonators do what their technicians say they are going to do. I install a lot of systems for Hollywood people, and their water has to be 100% right. With ClearWater, they're happy, they love their water, and that makes me happy!"*

Tito Ignacio, President of Wailani Natural Pure Water Systems - Burbank, CA

## Distributed by:

### Industrial Equipment

830 Cherry Street (800) 287-8306  
Chico, CA 95928



### M-15/AD

#### DESCRIPTION

Self contained, single reaction chamber CD ozone generator with built-in air dryer.

#### DIMENSIONS

19.5" h x 15.25" w x 7.5" d, 34 lbs

#### OZONE OUTPUT

2.8 grams/hr @ 7 SCFH (dry air)

### M-1500 & CD1500

#### DESCRIPTION

High output, single reaction chamber CD ozone generators. Suitable for use with dry air or oxygen air preparation options.

#### DIMENSIONS

27" h x 9.25" w x 5.5" d, 32 lbs

#### OZONE OUTPUT

**M-1500** - 2.8 grams/hr @ 7 SCFH (dry air)  
7.6 grams/hr @ 7 SCFH (PSA oxygen)  
**CD1500** - 4.5 grams/hr @ 10 SCFH (dry air)  
10 grams/hr @ 7 SCFH (PSA oxygen)



### CD1500P

#### DESCRIPTION

High output, pressurized, single reaction chamber CD ozone generator. Designed to operate at 10 psi cell pressure. Built-in pressure gauge and flow meter.

#### DIMENSIONS

27" h x 9.25" w x 5.5" d, 32 lbs

#### OZONE OUTPUT

15 grams/hr @ 6 SCFH  
(PSA oxygen) @ 10 psi