

K7 unloader sizing:

K7.0 2.11 - 2.91 gpm

K7.2 4.26 - 6.61 gpm

K7.1 2.91 - 4.23 gpm

K7.3 6.61-10.57 gpm

Note: Pressure Washers with float tanks will usually need 1 size smaller bypass orifice

Example: 4gpm machine with a float box usually needs a K7.1 with a 0 bypass orifice

No.	Desc	Part No.		Unloader	Orifice Size		
		IE	General		(mm)	(in)	drill #
21	Nipple	030-105	10.0078.70	K7.0	3	0.1181	31
		030-105	10.0078.70	K7.1	3	0.1181	31
		030-110	10.0160.70	K7.2	3.25	0.1280	30
		030-115	10.0161.70	K7.3	3.5	0.1378	28
23	Nozzle	030-085	10.0076.66	K7.0	2.2	0.0866	44
		030-090	10.0077.66	K7.1	2.5	0.0984	40
		030-095	10.0162.66	K7.2	2.75	0.1083	7/64 or 35
		030-100	10.0163.66	K7.3	3	0.1181	31
32	Bypass	030-120	36.3117.70	K7.0	3	0.1181	31
		030-125	36.3116.70	K7.1	4	0.1575	22
		030-130	36.3118.70	K7.2	5	0.1969	9
		030-135	36.3119.70	K7.3	7.5	0.2953	M

Distributed by: [Industrial Equipment](http://www.industrial-equipment.biz) 800-287-8306

830 Cherry Street, Chico, CA 95928 www.industrial-equipment.biz